Docket No.: JAEC-10213

Application No.: 10/810,478

Amendment Date: February 21, 2007 Reply of Office Action of: December 13, 2006

LISTING OF THE CLAIMS

This listing of the claims replaces all previous listings.

Claims 1-14 (Canceled)

Claim 15. (Currently amended) A motor vehicle comprising:

a motor vehicle body including a front end and a rear end of the motor vehicle

body, the motor vehicle body having a plurality of frame members with a skin of sheet material $\,$

covering the frame members and at least partially forming a generally vertical side wall, the

motor vehicle body extending from the front end to the rear end of the motor vehicle body in a

fore and aft direction generally parallel to a direction of travel of the motor vehicle, the motor vehicle body also extending laterally from side to side in a direction that is a generally

transverse direction relative to the direction of travel of the motor vehicle, wherein the motor

vehicle body includes a truck bed comprising at least a portion of the side wall;

at least one body receiver in the motor vehicle body, said body receiver having

structure forming the at least one body receiver, the structure of the body receiver defining a length extending in the transverse direction, the structure of the body receiver also defining an

opening in the motor vehicle body, wherein the opening has a width; and

the length of the body receiver being greater than the width of the opening of

the body receiver, said length of the body receiver extending in a direction that is generally horizontal and non-parallel to the fore and aft direction, wherein the body receiver opens out

away from a center of the motor vehicle through the side wall of the truck bed of the motor

at least one accessory selectively received in the at least one body receiver;

wherein

the receiver is not located in a bumper and the receiver is not a threaded

receiver; [[and]]

vehicle body;

Docket No.: JAEC-10213 Application No.: 10/810.478

Amendment Date: February 21, 2007

Reply of Office Action of: December 13, 2006

the receiver is located above a tire height of the motor vehicle[[.]]; the structure forming the at least one body receiver comprises a socket formed

by the opening disposed in the body; and

the accessory includes an insert connected to the accessory and selectively

located in the socket in a deployed state supporting the accessory on the body.

Claim 16. (Original) The motor vehicle of claim 15, wherein the accessory comprises

one or more of: a ladder rack, an electrician's reel, a barbeque accessory, a tool supporting table, a winch, a hunting accessory, a fishing accessory, a bike rack, a ski rack, a ramp, a width

extension, and a length extension,

Claim 17. (Canceled)

Claim 18. (Currently Amended) The motor vehicle of claim [[17]]15, wherein:

the structure provides the socket as a lengthwise horizontal socket; and

the insert comprises a shaft having a longitudinal axis disposed horizontally

when the insert is in the deployed state,

Claim 19. (Original) The motor vehicle of claim 18, wherein:

the body receiver is a first body receiver;

the motor vehicle further comprising a plurality of body receivers including

said first body receiver.

Claims 20. (Previously presented) The motor vehicle of claim 19, wherein the plurality

of body receivers comprises at least one lengthwise vertical socket.

Docket No.: JAEC-10213 Application No.: 10/810.478

Amendment Date: February 21, 2007

Reply of Office Action of: December 13, 2006

Claim 21. (Previously Presented) The motor vehicle of claim 20, wherein the plurality of body receivers comprises a plurality of lengthwise horizontal sockets including the

lengthwise horizontal socket.

Claims 22-26. (Canceled)

Claim 27. (Previously Presented) The motor vehicle of claim 19, wherein the plurality

of body receivers is added to the body of the vehicle.

Claim 28. (Original) The motor vehicle of claim 15, wherein the vehicle includes a

plurality of accessories including the at least one accessory.

Claim 29. (Canceled)

Claim 30. (Currently Amended) The motor vehicle of claim [[17]]15, further

comprising:

a hole in a wall of the socket:

a hole in the insert: and

a pin engaged through the hole in the wall of the socket and through the hole

in the insert to hold the insert in the socket against inadvertent separation therefrom.

Claims 31-43. (Canceled)

Docket No.: JAEC-10213 Application No.: 10/810.478

comprising:

Amendment Date: February 21, 2007

Reply of Office Action of: December 13, 2006

Claim 44. (Currently Amended) A motor vehicle having a truck bed, the truck bed

a front end and a rear end forming part of a motor vehicle body, the truck bed

having a plurality of frame members with a skin of sheet material covering the frame members,

the sheet material at least in part forming a side wall of the truck bed, the truck bed extending

from the front end to the rear end in a fore and aft direction generally parallel to a direction of

travel of the motor vehicle, the truck bed also extending laterally from side to side in a direction

that is a generally transverse direction relative to the direction of travel of the motor vehicle;

at least one body receiver in the truck bed, said body receiver having structure

forming the at least one body receiver, the structure of the body receiver defining a length extending in the transverse direction, the structure of the body receiver also defining an opening

in the truck bed, wherein the opening has a width; and

the length of the body receiver being greater than the width of the opening of

the body receiver, said length of the body receiver extending in a direction that is generally

horizontal and non-parallel to the fore and aft direction, wherein:

the body receiver opens out away from a center of the motor vehicle through

the side wall; and

the body receiver is not located in a bumper; and

at least one accessory selectively received in the at least one body

receiver[[.]]; wherein

the structure forming the at least one body receiver comprises a socket formed

by the opening disposed in the body;

the accessory includes an insert connected to the accessory and selectively

 $\underline{located\ in\ the\ socket\ in\ a\ deployed\ state\ supporting\ the\ accessory\ on\ the\ body}.$